

SApperloT

Description of solver SApperloT
submitted for the SAT-Race 2010
Stephan Kottler and Christian Zielke

Eberhard Karls Universität Tübingen, Germany
{kottlers,zielke}@informatik.uni-tuebingen.de

The main issues of SApperloT

The submitted version of SApperloT extends the hybrid SApperloT solver that participated at the sat competition 2009[5]. The solver is written in C++ and was submitted as a 32-bit version for the competition.

SApperloT is a hybrid solver that combines the idea of reference points with conflict-driven solving with clause learning (CDCL). Decision making with reference points (DMRP) was proposed by Goldberg [3, 4]. DMRP offers an appropriate method to analyse partial assignments during search: When the CDCL algorithm performs a restart the assignment stack is extended to a complete assignment R - a so-called reference point that we choose to fulfill all binary clauses at first stage. This complete assignment is then taken as an initial reference point for the DMRP algorithm. In difference to state-of-the-art CDCL the DMRP approach bases its decisions on the set of clauses that is not satisfied by a current reference point. Even though DMRP requires some extra information for solving this can give a good direction for the search. More details can be found in [6].

The CDCL implementation uses state-of-the-art techniques like phase saving and Luby restarts [7, 8, 10, 2, 9, 1]. We use our own preprocessor that runs for a maximum of 100 cpu-seconds to simplify a given instance.

References

- [1] Armin Biere. Picosat essentials. *JSAT*, 4:75–97, 2008.
- [2] Niklas Eén and Niklas Sörensson. An extensible SAT-solver. In *SAT 2003*, 2003.
- [3] Eugene Goldberg. Determinization of resolution by an algorithm operating on complete assignments. In *SAT 2006*, 2006.
- [4] Eugene Goldberg. A decision-making procedure for resolution-based SAT-solvers. In *SAT 2008*, 2008.

- [5] Stephan Kottler. Solver descriptions for the SAT competition 2009. satcompetition.org.
- [6] Stephan Kottler. SAT Solving with Reference Points. In *SAT 2010*, 2010.
- [7] Joao P. Marques-Silva and Karem A. Sakallah. Grasp: A search algorithm for propositional satisfiability. *IEEE Trans. Comput.*, 48(5):506–521, 1999.
- [8] Matthew W. Moskewicz, Conor F. Madigan, Ying Zhao, Lintao Zhang, and Sharad Malik. Chaff: engineering an efficient SAT solver. In *DAC*, 2001.
- [9] Knot Pipatsrisawat and Adnan Darwiche. Rsat 2.0. In *Solver Description*, 2007.
- [10] Niklas Sörensson and Niklas Eén. Minisat - a SAT solver with conflict-clause minimization. In *Solver Description*, 2005.